

Safety Data Sheet

Section 1 - Product and Company Identification

Material Name Product Code Product Description	* RX-981 Butter-Flash Adhesive and Sealant * RX-981 * Liquid.
Product Use	* Elastomeric Sealant
Synonyms	* Roof Membrane
Manufacturer	* Gardner Gibson 4701 E. 7th Avenue Tampa, FL 33605 United States www.gardner-gibson.com Please use "Contact Us" form on the website
Telephone	
Technical	* 813-248-2101
<u>Emergency</u>	* 800-424-9300
<u>Emergency</u>	* 703-527-3887
Preparation Date	* 5/10/2016
Last Revision Date	* 5/10/2016

Section 2 - Hazards Identification

Emergency Overview

WARNING

Causes mild skin irritation. Harmful if swallowed.

- PreventionDo not handle until all safety precautions have been read and understood. Use personal
protective equipment as required. Wash thoroughly after handling.
- **Response** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention.

Storage/Disposal Store in a closed container. Do not allow product to freeze. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.



Classification:

Eye irritation, Category 2A Skin sensitization, Category 1 Carcinogenic, Category 2

Statements of Hazard:

Warning H319 Causes serious eye irritation H317 May cause allergic skin reaction H351 Suspected of causing cancer

Precautions for Safe Handling: P102 Keep out of the reach of children

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P261 Avoid breathing vapors or mists P264 Wash hands thoroughly after handling

P272 Contaminated work clothing should not be allowed out of the workplace P281 Use personal protective equipment as required

CAUTION - May cause eye and skin irritation on contact.

Physical Form	* Liquid
Color	* Liquid.
Odor	* Paint-Like Odor.
Flash Point	* 247 F
OSHA	* Irritant
WHMIS	* Class D - Poisonous and Infectious Materials - Division 2 - Subdivision B
	$\overline{\mathbf{T}}$
GHS	 * Skin Corrosion/Irritation - Category 1 Serious Eye Damage, Eye Irritation - Category 2A Carcinogenic – Category 2B
NFPA:	Health : 2 Flammability: 1 Reactivity: 0 Personal Protection: G

Potential Health Effects

Inhalation Acute (Immediate) Chronic (Delayed)	 * Inhalation of vapors or mists may cause central nervous system depression, light- headedness, headache, nausea and loss of coordination. * Under normal conditions of use, no health effects are expected.
Skin Acute (Immediate) Chronic (Delayed)	 * May cause irritation. * Repeated and prolonged exposure to the skin may cause dermatitis.
Eye Acute (Immediate)	* Likely to cause eye irritation, burning, tearing, etc. on contact with the eyes. If swelling and irritation persist, seek medical attention.

Chronic (Delayed)

- * Direct contact may cause slight to moderate irritation.
- IngestionAcute (Immediate)* May cause irritation. May affect the nervous system. May be harmful or fatal if
swallowed.Chronic (Delayed)* Repeated and prolonged exposure may cause gastrointestinal disturbances
including diarrhea, nausea, and vomiting.

Carcinogenic Effects					
CAS IARC NTP					
Titanium Dioxide	13463-67-7	Group 2B-Possible Carcinogen	Evidence of Carcinogenicity		

Section 3 - Composition/Information on Ingredients

Hazardous Components						
Chemical Name Identifiers %		%(weigh t)	LD50/LC50	Classifications According to Regulation/Directive	Comment s	
Sylil-Terminated Poly Ether	CAS: 151865-59-7	40.0%	LD50 Oral - rat - > 3160 mg/kg			
Silica Quartz	CAS: 68476-25-5	54.0%				
Dinonyl Phthalate	CAS: 84-76-4	3.0%				
Titanium Dioxide	CAS: 13463-67-7	1.0%	LD50 Oral, rat · 60 gm/kg			
Black Iron Oxide	CAS: 12227-89-3	0.5%				
Fumed Silica	CAS: 112945-52-5	1.0%	LD50 Oral - rat - > 3160 mg/kg			
Aminopropyl Trimethoxy Silane	CAS: 13822-56-5	0.5%	LD50 Oral - rat - > 62.080 mg/kg			

Non-Hazardous Components						
Chemical Name Identifiers %(weight) LD50/LC50 Classifications According to Regulation/Directive Comme						

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Section 4 - First Aid Measures

Inhalation	* IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If signs/symptoms continue, get medical attention.
Skin	* Rinse skin immediately with plenty of water for 15-20 minutes. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
Еуе	* If eye irritation persists: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Ingestion	* If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Section 5 - Fire Fighting Measures

Extinguishing Media	 * LARGE FIRE: Water spray, fog or regular foam. SMALL FIRES: Dry chemical, CO2, water spray or regular foam.
Unsuitable Extinguishing Media	* No data available.
Firefighting Procedures	 Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Keep unauthorized personnel away.
Unusual Fire and Explosior Hazards	 Product containers may rupture when exposed to extreme heat. Precaustions should be taken to prevent release of materials.
Hazardous Combustion Products	 * Non-combustible, substance itself does not burn but may decompose upon heating to produce toxic fumes.
Protection of Firefighters	 Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.
Flash Point	* 247 F(85 C) CC (Closed Cup)

Section 6 - Accidental Release Measures

Personal Precautions	* Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
Emergency Procedures	* Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up.
Environmental Precautions	* Avoid run off to waterways and sewers.
Containment/Clean-up Measures	 * Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use appropriate Personal Protective Equipment (PPE)
Prohibited Materials	* Avoid contact with strong oxidizing agents and acids.

Section 7 - Handling and Storage

Handling	* KEEP OUT OF THE REACH OF CHILDREN! Keep containers tightly closed when not in use.
Storage	* Avoid extreme temperatures and freezing. Keep container/package tightly closed and in a well-ventilated place.
Special Packaging Materials	* Not Applicable.
Incompatible Materials or Ignition Sources	* Avoid contact with strong oxidizing agents and acids.

Section 8 - Exposure Controls/Personal Protection

Personal Protective Equipment

Pictograms	* 🖛 📨 🔺 🥪
Respiratory	* Use with adequate ventilation. A respirator is required. Use a NIOSH-approved air purifying respirator with organic vapor cartridge or supplied air respirator. This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.
Eye/Face	* Wear ANSI approved safety glasses with side shields or safety goggles.

* Wear chemical resistant gloves with repeated or prolonged exposure.

Engineering Measures/Controls

* Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Use precaution to protect building intake from fumes and vapors created outdoors.

Exposure Limits/Guidelines						
	Result Canada Ontario Mexico NIOSH OSHA					
Titanium Dioxide (13463-67-7)	IVVAS	dust)	11)	10 mg/m3 - TWA	15 mg/m3 TWA (total dust)	
Black Iron Oxide (12227-89-3	TWAs	10 mg/m3 TWAEV (Total Dust)	10 mg/m3 TWA	10 mg/m3 TWA	10 mg/m3	
Fumed Silica (112945-52-5)	TWAs	10 mg/m3-TWAEV	10 mg/m3 TWA	6 mg/m3-TWA	6 mg/m3-TWA	

Section 9 - Physical and Chemical Properties

Material Description				
Physical Form	Liquid	Appearance/Description	liquid with heavy consistency.	
Color	White Liquid.	Odor	Paint-Like Odor.	
Taste	No data available.	Particulate Type	Not relevant	
Particulate Size	Not relevant	Aerosol Type	Not relevant	
Odor Threshold	No data available			
General Properties	•	•		
Boiling Point	>300 F	Melting Point	No data available	
Decomposition Temperature	No data available	Heat of Decomposition	Not relevant	
рН	8 @ 25 C(77 F)	Specific Gravity/Relative Density	1.50 Water=1	
Density	12.55 lbs/gal @ 25 C(77 F)	Bulk Density	No data available	
Water Solubility	Soluble 0 % @ 25 C(77 F)	Solvent Solubility	Not relevant	
Viscosity	124,000 cps. @ 25 C(77 F)			
Volatility				
Vapor Pressure	5.3 mmHg (torr) @ 20 C(68 F)	Vapor Density	> 1 Air=1	
Evaporation Rate	< 0.7 Ether = 1	VOC (Wt.)	No data available	
VOC (Vol.)	<10 g/L	Volatiles (Wt.)	No data available	
Volatiles (Vol.)	No data available			
Flammability				
Flash Point	247 F	Flash Point Test Type	CC (Closed Cup)	
UEL	No data available	LEL	No data available	
Autoignition	No data available	Self-Accelerating Decomposition Temperature (SADT)	Not relevant	
Heat of Combustion (ΔHc)	Not relevant	Burning Time	Not relevant	
Flame Duration	Not relevant	Flame Height	Not relevant	
Flame Extension	Not relevant	Ignition Distance	Not relevant	
Environmental	•	•		
Half-Life	Not relevant	Octanol/Water Partition coefficient	Not relevant	
Coefficient of Water	Not relevant	Bioaccumulation Factor	Not relevant	
Bioconcentration Factor	Not relevant	Biochemical Oxygen Demand BOD/BOD5	Not relevant	
Chemical Oxygen Demand	Not relevant	Persistence	Not relevant	
Degradation	Not relevant			

Section 10 - Stability and Reactivity

Stability	* Stable under normal temperatures and pressures.
Hazardous Polymerization	 * Hazardous polymerization not indicated.
Conditions to Avoid	* Excessive heat and freezing.
Incompatible Materials	* Strong oxidizers and acids.
Hazardous Decomposition Products	* No known issues under normal usage conditions.

Section 11 - Toxicological Information

Component Name	CAS	Data
Sylil-Terminated Poly Ether	151865-59-7	Acute Toxicity: LD50 Oral - rat - > 3160 mg/kg
Fumed Silica	112945-52-5	Acute Toxicity: LD50 Oral - rat - > 3160 mg/kg
Titanium Dioxide	13463-67-7	Acute Toxicity: LD50 Oral, rat · 60 gm/kg
Aminopropyl Trimethoxy Silane	13822-56-5	Acute Toxicity: LD50 Oral - rat - > 62.080 mg/kg

Other Component Information

* IARC has concluded that the following chemicals in this product are carcinogenic to humans(Group 1): ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz. NTP has listed the following chemicals in this product as known human carcinogens:. Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.

Section 12 - Ecological Information

Ecological Fate	* No data available.
Persistence/Degradability	* No data available.
Bioaccumulation Potential	* No data available.
Mobility in Soil	* No data available.
Other Information	* Do not allow product exposure to the ground or into any waterway. Do not allow entry into municipal sewer systems.

Section 13 - Disposal Considerations

Product

* Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transportation Information

DOT - United States - Department of Transportation - Shipping Name: Not Regulated.

TDG - Canada - Transportation of Dangerous Goods - Shipping Name: Not Restricted.

IMO/IMDG - International Maritime Transport Shipping Name: Not Regulated.

International Air Transportation Association – Not Regulated

Section 15 - Regulatory Information

State Right To Know					
Component	CAS	MA	MN	NJ	PA
Sylil-Terminated Poly Ether	151865-59-7	Yes	Yes	Yes	Yes
Silica Quartz	68476-25-5	Yes	Yes	Yes	Yes
Dinonyl Phthalate	84-76-4	Yes	Yes	Yes	Yes
Titanium Dioxide	13463-67-7	Yes	Yes	Yes	Yes
Fumed Silica	112945-52-5	Yes	Yes	Yes	Yes
Black Iron Oxide	12227-89-3	Yes	Yes	Yes	Yes
Aminopropyl Trimethoxy Silane	13822-56-5	Yes	Yes	Yes	Yes

SARA Hazard Classifications * Acute, Chronic

Inventory			
Component	CAS	EU EINECS	TSCA
Sylil-Terminated Poly Ether	151865-59-7	Yes	Yes
Silica Quartz	68476-25-5	Yes	Yes
Dinonyl Phthalate	84-76-4	Yes	Yes
Titanium Dioxide	13463-67-7	Yes	Yes
Black Iron Oxide	12227-89-3	Yes	Yes
Fumed Silica	112945-52-5	Yes	Yes
Aminopropyl Trimethoxy Silane	13822-56-5	Yes	Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

Sylil- Terminated Poly Ether	151865-59-7	D2B
Silica Quartz	68476-25-5	D2B
Dinonyl Phthalate	84-76-4	D2B
Titanium Dioxide	13463-67-7	D2A

United States

Environment

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

Silica Quartz	68476-25-5
Sylil-	
Terminated	151865-59-7
Poly Ether	

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List Sylil-Terminated 151865-59-7 Poly Ether

United States - Rhode Island

Labor

U.S. - Rhode Island - Hazardous Substance List Titanium Dioxide Fumed Silica 112945-52-5

Aminopropyl Trimethoxy 13822-56-5 Silane

Other Information

* WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Preparation Date Last Revision Date Disclaimer/Statement of Liability	 5/10/2016 5/10/2016 This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the users responsibility to verify the suitability and completeness of such information for particular use. Gardner-Gibson does not accept liability for any loss or damage that may occur from the use of this information.